

QMS Video Validation Tool



USER MANUAL

Copyright

This manual, Copyright © 2024 Unigraf Oy. All rights reserved

Reproduction of this manual in whole or in part without a written permission of Unigraf Oy is prohibited.

Notice

The information given in this manual is verified in the correctness on the date of issue. The authors reserve the right to make any changes to this product and to revise the information about the products contained in this manual without an obligation to notify any persons about such revisions or changes.

Edition

QMS Video Validation Tool, Version 1

Date: 27 June 2024

Company Information

Unigraf Oy

Piispantilankuja 4
FI-02240 ESPOO
Finland

Tel. +358 9 859 550

<mailto:info@unigraf.fi>

<https://www.unigraf.fi>

<http://www.unigraf-china.cn>

Trademarks

Unigraf, UCD, TSI and TSI Lite are trademarks of Unigraf Oy.

HDMI is a trademark of HDMI Licensing, LLC.

Windows® 10, Windows® 8, Windows® 7 and Windows® XP are trademarks of Microsoft Corporation.

All other trademarks are properties of their respective owners.

Limited Warranty

Unigraf warrants its hardware products to be free from defects in workmanship and materials, under normal use and service, for twelve (12) months from the date of purchase from Unigraf or its authorized dealer.

If the product proves defective within the warranty period, Unigraf will provide repair or replacement of the product. Unigraf shall have the whole discretion whether to repair or replace, and replacement product may be new or reconditioned. Replacement product shall be of equivalent or better specifications, relative to the defective product, but need not to be identical. Any product or part repaired by Unigraf pursuant to this warranty shall have a warranty period of not less than 90 days, from the date of such repair, irrespective of any earlier expiration of original warranty period. When Unigraf provides replacement, then the defective product becomes the property of Unigraf.

Warranty service may be obtained by contacting Unigraf within the warranty period. Unigraf will provide instructions for returning the defective product.

Table of Contents

1.	About This Manual	5
2.	Background.....	6
3.	Software Installation	7
4.	Video Recording	8
5.	Running the Tool	10
6.	Understanding Failures.....	11
7.	Logging.....	12
	Version History	13

1. ABOUT THIS MANUAL

Purpose

This guide is the User Manual of QMS Video Validation Tool (QMS VVT), a software tool for use in a PC with Windows®, Linux, and other operating systems where Python can be used.

The purpose of this guide is to

- Provide instructions for the user on how to install the software.
- Provide instructions for the user on how to use the tool.

Product and Driver Version

This manual explains features found in QMS VVT **1. 0**. Please consult Unigraf for differences or upgrades of previous versions.

Notes

On certain sections of the manual, when important information or notification is given, text is formatted as follows. Please read these notes carefully.

Note	This text is an important note
------	--------------------------------

2. BACKGROUND

HDMI GCTS QMS-VRR transition and tolerance tests HF2-73, HFR2-73, HF2-77, and HFR2-77 require validation of the video displayed by the Sink DUT.

To validate that video is not corrupted when QMS transition happen, a high-speed video should be recorded and verified that video is stable, and no video frames are dropped. Manual validation by frame-by-frame scrolling through video is tiresome. The purpose of this tool is to automate validation.

The tool was designed to analyse patterns generated by Unigraf test equipment UCD-323 or UCD-422. See Unigraf MOI documents for more details.

3. SOFTWARE INSTALLATION

Prerequisites

1. Install Python 3.9 or later
2. Install OpenCV package:
 - `pip install opencv-python`
3. Install matplotlib:
 - `pip install matplotlib`

Installation Package

This QMS VVT software zip archive can be obtained from Unigraf download page at <https://www.unigraf.fi/moi/>

The archive contains the following items:

- `main.py` – the tool itself, it's a Python script
- Sample videos in the *samples* directory
- `QMSVideoCheck.pdf` – this User Manual.

Software Installation

Download the `QMSVVT.zip` and uncompress it.

4. VIDEO RECORDING

High Speed Camera

A camera capable of video recording 240fps is required. Consumer cameras like SONY DSC-RX100 Mark V and similar should be considered as an alternative to mobile phones. Even though there are mobile phones capable of 240fps video recording, noise level is not always acceptable.

Dark environment

Recording should be done in a dark environment to avoid visible reflections on the screen.

Camera shake

Camera shaking is not acceptable. A camera should be mounted on a tripod.

Camera position

A camera should be placed perpendicularly to the DUT screen.

A camera should be targeted at the center of the screen.

The entire screen should fit in the recorded video.

Examples




Figure 1 An example of acceptable video recording.

UNIGRAF



Figure 2 An example of not acceptable recording: there are reflections on the screen, and the camera is not placed perpendicularly to the screen. Also, the image is noisy.

5. RUNNING THE TOOL

Execute the command

➤ `python main.py <video_file_name>`

The recorded video should be provided in common formats – mp4, mov, avi.

If the command line argument is not provided, the tool analyses a sample video provided with the tool.

After loading the video, the following dialog with a combined image of multiple overlapping frames is shown. Using a mouse, please select the entire screen of the TV under test (note the blue rectangle selection) and press ENTER when done.




Figure 3 Frame area selection.

Then the analysis begins, and the following window is shown. The software analyses the 1st (i.e. the upper) and the 3rd rows of rectangles on the test pattern.




Figure 4 Analysis in progress.

When completed, the result is printed in the console:




Figure 5 Successful test.

6. UNDERSTANDING FAILURES

For each frame where an error is detected, six files are written to the *failed* directory. They are:

- The failed frame e.g. **fail.jpg*
- A previous frame **previous.jpg*
- The region of interest (ROI) of the failed frame *1st*fail.jpg*
- The ROI of the previous frame *1st*previous.jpg*
- A threshold mask of the failed frame *1st*thresh.jpg*
- A threshold mask of the previous frame *1st*thresh0.jpg*

There may be cases of false error detection due to imperfections in video recording. It is recommended to review the failed frames and compare them with previous ones. Below is an example of such a false error detection. The failed frame is correct – it shows that the next square appears in the expected position, next to the previous.

	Previous	Failed
ROI		
Threshold mask		

7. LOGGING

The script writes a log in the current directory in the *analyzer.log* file.

VERSION HISTORY

Rev.	Date	Author	Description
1	27.06.2024	VKh	- Initial version of manual.
			-
			-
			-
			-
			-
			-
			-
			-
			-
			-
			-
			-